



DISTRIBUTED BY CLEARLAKE SUPPLY

847.686.2890

FEATURES

- 100% Recycled Crumb Rubber .8mm-1.5mm
- Suitable for most Rooftop Material*
- UV Resistant
- Noise/Vibration Dampening
- Highly Resistant to Freeze/Thaw

APPLICATIONS

- Solar Racking
- HVAC Ducting
- HVAC System Support
- Pipe/Conduit Support
- Cable Tray Systems
- Roof Walkway Systems
- Data Centers

INDEPENDENT LAB TESTING

- Ozone Exposure ASTM D1149-18
- Heat Aging ASTM D573-2019
- Hardness (Durometer Shore A) ASTM D2240-2021
- Compressive Strength ASTM D395-2018
- Tensile Testing ASTM D412-2016

FINISHES

- Pre-Galvanized Steel Strut
- Other special order finishes available

MODEL	STRUT LENGTH	BLOCK LENGTH	HEIGHT	WIDTH	LOAD CAPACITY*	WEIGHT
<input type="checkbox"/> T210C	9.6"	10.5"	5"	5"	2,500LBS	5.36LBS
<input type="checkbox"/> T205C	5"	6"	5"	5"	400LBS	2.82LBS



MODEL T210C



MODEL T205C

*Uniform block load capacity only. Always consult engineer for substrate load capacity. Consult roofing material manufacturer for compatibility.

