

# STURDY FOOT™ KITS



DISTRIBUTED BY CLEARLAKE SUPPLY

847.686.2890

## FEATURES

- Vulcanized Recycled Rubber
- Suitable for most Rooftop Material\*
- UV Resistant
- Noise/Vibration Dampening
- Highly Resistant to Freeze/Thaw
- Indented hand hold design/easy transportation
- Includes Hardware for mounting to mini split units
- Optional Reflector

## FINISHES

- Pre-Galvanized Steel Strut
- Other special order finishes available.

## APPLICATIONS

- HVAC Unit Mounting
- Solar Racking
- HVAC Ducting
- HVAC System Support
- Pipe/Conduit Support
- Cable Tray Systems
- Roof Walkway Systems
- Data Centers

## INDEPENDENT LAB TESTING

- Ozone Exposure ASTM D1149-18
- Heat Aging ASTM D573-2019
- Hardness (Durometer Shore A) ASTM D2240-2021
- Compressive Strength ASTM D395-2018
- Tensile Testing ASTM D412-2016

MODEL	STRUT LENGTH	BLOCK LENGTH	HEIGHT	WIDTH	LOAD CAPACITY**	WEIGHT
<input type="checkbox"/> T316V-KIT	16"	16"	4"	6"	3,000LBS	17 LBS
KIT CONTAINS (2) T316V AND MOUNTING HARDWARE						
<input type="checkbox"/> T318V-KIT	18"	18"	4"	6"		
KIT CONTAINS (2) T318V AND MOUNTING HARDWARE						
<input type="checkbox"/> T324V-KIT	22.5"	23.5"	4"	6"	4,000LBS	23 LBS
KIT CONTAINS (2) T324V AND MOUNTING HARDWARE						



\*Consult Roofing material manufacturer for material compatibility.

\*\*Uniform block load capacity only. Always consult engineer for substrate load capacity. Mounting holes not rated to hold load capacity.

