STURDY FOOT™

TALON ROOFING PRODUCTS

DISTRIBUTED BY CLEARLAKE SUPPLY **847.686.2890**

FEATURES

- Vulcanized Recycled Rubber
- Suitable for most Rooftop Material*
- UV Resistant
- Noise/Vibration Dampening
- Highly Resistant to Freeze/Thaw
- Reflector for hi visibility
- Indented hand hold design/easy transportation

APPLICATIONS

- HVAC Unit Mounting
- Solar Racking
- HVAC Ducting
- HVAC System Support
- Pipe/Conduit Support
- Cable Tray Systems
- Roof Walkway Systems
- Data Centers

INDEPENDENT LAB TESTING

- Ozone Exposure ASTM D1149-18
- Heat Aging ASTM D573-2019
- Hardness (Durometer Shore A) ASTM D2240-2021
- Compressive Strength ASTM D395-2018
- Tensile Testing ASTM D412-2016

FINISHES

- Pre-Galvinized Steel Strut
- Other special order finishes available

MODEL	STRUT LENGTH	BLOCK LENGTH	HEIGHT	WIDTH	LOAD CAPACITY**	WEIGHT
☐ T310V	10"	10"	4"	6"	2000LBS	5.8LBS
☐ T316V	16"	16"	4"	6"	1,500LBS	7.87LBS
☐ T318V	18"	18"	4"	6"		
☐ T324V	22.5"	23.5"	4"	6"	2,000LBS	11.12LBS
☐ T330V	28.5"	29.5"	4"	6"		
☐ T340V	38.5"	39.5"	4"	6"		

MODEL
T316V

*Consult Roofing material manufacturer for material compatibility.
**Uniform block load capacity only. Always consult engineer for substrate load capacity. Mounting holes not rated to hold load capacity.

www.talonroofingproducts.com info@talonroofingproducts.com